



LEGENDARY PERFORMANCE | VERSATILE PERFORMANCE TO TACKLE ANY TERRAIN



RZR TRAIL SPORT - 50"



RZR TRAIL S 1000 PREMIUM - 60"



RZR XP 1000 SPORT - 64"



MY24 RZR XP 1000 PREMIUM - 64"



RZR PRO XP SPORT - 64"



RZR PRO XP ULTIMATE - 64"



RZR TURBO R ULTIMATE - 74"



RZR PRO R ULTIMATE - 74"

HORSEPOWER	75 HP	100 HP	110 HP	114 HP	181 HP	181 HP	181 HP	225 HP
ENGINE	875cc	999cc	999cc	999cc	925cc	925cc	925cc	1997cc
DRIVE SYSTEM	High Performance True On-Demand AWD/2WD	High Performance True On-Demand AWD/2WD	High Performance On-Demand True AWD/2WD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On-Demand AWD/2WD	Pro Performance True 2WD/4WD/4WD Lock
ENGINE BRAKING SYSTEM / ACTIVE DESCENT CONTROL	Yes / Not Equipped	Yes / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped/ Not Equipped	Not Equipped/ Not Equipped	Not Equipped/ Not Equipped
FRONT SUSPENSION	Dual A-Arm with Stabilizer Bar and 25.4 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 31.1 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel, 40.6 cm of Wheel Travel	Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel, 40.6 cm of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm *Usable Travel, 43.2 cm Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm *Usable Travel, 43.2 cm Wheel Travel	Light Weight Boxed Dual A-Arm with 3 Piece Stabilizer Bar and 68.6 cm Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm *Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs
REAR SUSPENSION	Dual A-Arm with Stabilizer Bar and 25.4 cm Wheel Travel	Dual A-Arm with Stabilizer Bar and 33.5 cm Wheel Travel	Trailing Arm with Stabilizer Bar and 50.8 cm Usable Travel, 45.7 cm of Wheel Travel	Trailing Arm with Stabilizer Bar and 50.8 cm Usable Travel, 45.7 cm of Wheel Travel	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm *Usable Travel, 50.8 cm Wheel Travel	Trailing Arm & Standard-Clearance Radius Rods with Stabilizer Bar and 55.9 cm *Usable Travel, 50.8 cm Wheel Travel	Tubular Trailing Arm with boxed gusseting and Toe Link, High Clearance Radius Rods, and Stabilizer Bar and 71.9cm Usable Travel, 56.9 cm Wheel Travel, Unitized Hubs	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 Piece Stabilizer Bar and 73.7 cm *Usable Travel, 62.2 cm Wheel Travel, Unitized Hubs
DYNAMIX ACTIVE SUSPENSION	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Not Equipped	Yes	Yes	Yes
SHOCKS	ZF Twin Tube	Fox 2.0	Walker Evans	Walker Evans	Fox 2.0 Front / 2.5 Rear	FOX 2.5 Live Valve	Fox 3.0 Live Valve	Fox 3.0 Live Valve X2
WHEELBASE	200.7 cm	200.7 cm	228.6 cm	228.6 cm	244 cm	244 cm	244 cm	265.4cm
TYRES	26" PXT	27" Trailmaster A/T	29" Radial Tires	30" Trail Master X/T 2.0	30 Maxxis Carnivore"	30" Maxxis Carnivore (8-Ply Rated)	32" Maxxis Rampage Fury (8-Ply Rated)	32" Maxxis Rampage Fury (8-Ply Rated)
DRY WEIGHT	561.5 kg	600 kg	662 kg	742.5 kg	798 kg	814 kg	913 kg	992 kg
OVERALL VEHICLE SIZE (L X W X H)	282 x 127 x 172.5 cm	282 x 152.4 x 176 cm	302.2 x 162.6 x 187.3 cm	304.8 x 162.6 x 188 cm	320 x 162.6 x 182.1 cm	320 x 163 x 182 cm	325 x 188 x 189 cm	347 x 188 x 185 cm
GROUND CLEARANCE	27.9 cm	31.8 cm	35.6 cm	36.8 cm	36.8 cm	36.8 cm	40.6 cm	40.6 cm
SEATING CAPACITY	2	2	2	2	2	2	2	2
FUEL CAPACITY	35.9 L	35.9 L	35.9 L	36 L	45.4 L	45.4 L	45.4 L	45.4 L
FRONT/REAR RACK OR BOX CAPACITY	N/A / 131 kg	N.A / 136 kg	N/A / 136.1 kg	N/A / 136 kg	N/A / 136 kg	N/A / 136 kg	N/A / 136 kg	N/A / 136 kg
PAYLOAD CAPACITY	335.7 kg	336 kg	336 kg	336 kg	336 kg	336 kg	336 kg	335.6 kg
HITCH TOWING RATING	680 kg	680 kg	N/A	N/A	N/A	N/A	N/A	N/A
ELECTRONIC POWER STEERING	Not Equipped	Yes	Standard with Quick Turn Rack	Standard with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Push Button Controls	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Ride Command Push Button Controls	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt and Telescoping Adjustment; DYNAMIX DV with Integrated EPS Modes and Push Button Controls

*Specifications subject to change.





LEGENDARY PERFORMANCE | VERSATILE PERFORMANCE TO TACKLE ANY TERRAIN



RZR XP 4 1000 SPORT - 64"



MY24 RZR XP 4 1000 PREMIUM - 64"



RZR PRO XP 4 SPORT - 64"



RZR PRO XP 4 ULTIMATE - 64"



RZR PRO R 4 ULTIMATE - 74"

HORSEPOWER	110 HP	114 HP	181 HP	181 HP	225 HP
ENGINE	999cc	999cc	925cc	925cc	1997cc
DRIVE SYSTEM	High Performance On-Demand True AWD	High Performance True On-Demand AWD/2WD	Isolated Xtreme Performance True On- Demand AWD/2WD	Isolated Xtreme Performance True On- Demand AWD/2WD	Pro Performance True 2WD/4WD/4WD Lock
ENGINE BRAKING SYSTEM / ACTIVE DESCENT CONTROL	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped	Not Equipped / Not Equipped
FRONT SUSPENSION	Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel, 40.6 cm of Wheel Travel	Dual A-Arm with Stabilizer Bar and 52.07 cm *Usable Travel, 40.6 cm of Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel	High-Clearance Dual A-Arm with Stabilizer Bar and 50.8 cm Usable Travel*, 43.2 cm Wheel Travel	Light Weight Boxed Dual A-Arm with 3 piece Stabilizer Bar and 68.6 cm *Usable Travel, 56.5 cm Wheel Travel, Unitized Hubs
REAR SUSPENSION	Trailing Arm with Stabilizer Bar and 50.8 cm Usable Travel, 45.7 cm of Wheel Travel	Trailing Arm with Stabilizer Bar and 52.07 cm Usable Travel*, 45.7 cm of Wheel Travel	Trailing Arm & Standard- Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel	Trailing Arm & Standard- Clearance Radius Rods with Stabilizer Bar and 55.9 cm Usable Travel*, 50.8 cm Wheel Travel	Boxed Trailing Arm with Toe Link, High-Clearance Radius Rods, and 3 Piece Stabilizer Bar and 73.7 cm *Usable Travel, 62.2 cm Wheel Travel, Unitized Hubs
DYNAMIX ACTIVE SUSPENSION	Not Equipped	Not Equipped	Not Equipped	Yes	Yes
SHOCKS	Walker Evans	Walker Evans	Fox 2.0 Front / 2.5 Rear	Fox 2.5 Live Valve	Fox 3.0 Live Valve
WHEELBASE	297.2 cm	297.2 cm	317.5 cm	317.5 cm	339.1 cm
TYRES	29" Radial Tires	30" Trail Master X/T 2.0	30 x 10-14 Maxxis Carnivore II; (8-ply rated)	30 x 10-14 Maxxis Carnivore II; (8-ply rated)	32" Maxxis Rampage Fury (8-Ply Rated)
DRY WEIGHT	758 kg	860 kg	916 kg	937 kg	1105.4 kg
OVERALL VEHICLE SIZE (L X W X H)	370.8 x 162.6 x 187.3 cm	375.4 x 162.6 x 190.5 cm	393.7 x 162.6 x 186.9 cm	393.7 x 162.6 x 186.9 cm	420 x 188 x 194 cm
GROUND CLEARANCE	35.6 cm	36.8 cm	36.8 cm	36.8 cm	40.6 cm
SEATING CAPACITY	2	4	4	4	4
FUEL CAPACITY	35.9 L	36 L	49.2 L	49.2 L	46.56 L
FRONT/REAR RACK OR BOX CAPACITY	N/A / 136.1 kg	136 kg	N/A / 136 kg	N/A / 136 kg	136.1 kg
PAYLOAD CAPACITY	408 kg	408 kg	408 kg	408 kg	408 kg
HITCH TOWING RATING	N/A	N/A	N/A	N/A	N/A
ELECTRONIC POWER STEERING	Standard with Quick Turn Rack	Standard with Quick Turn Rack	High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel	High Assist Electronic Power Steering with Quick Turn Rack; Race inspired Steering Wheel with Tilt and Telescoping adjustment; Dynamix and Ride Command Push Button Controls	Rack Mounted High Assist Electronic Power Steering with Quick Turn Rack; Race Inspired Steering Wheel with Tilt & Telescoping Adjustment; Push Button Controls

*Specifications subject to change.

